



Image Plus UV100



ImagePlus completely filters the harmful UV rays unlike conventional products such as float glass. It is ideal for use as UV Blocking acrylic for conservation framing and museum case protection.

ImagePlus is produced using a unique proprietary process & in application it allows less than 1% UV transmission. This makes it a unique acrylic product that is lightweight, easy to cut & install and has high impact strength in comparison to glass.

Features

- Excellent clarity
- 99.7% UV resistant
- Strong
- Easy to cut & install
- Lightweight

Applications

- Museum display
- Picture framing
- Signage & display
- Furniture & joinery
- Flat applications only

COLOUR RANGE *(May not represent the physical product.)*



PRODUCT RANGE/DIMENSIONS		
Type	Thickness	Length & Width
Clear	3.0mm	2440mm x 1220mm

PANEL PHYSICAL PROPERTIES	
Type	Result
Density	1.19g/cm ³
Weight (3.0mm)	3.69kg/m ²
Gauge Tolerance	+/- 2%
Light Transmission	92%
Service Temperature	70°C
Vicat Softening Temperature	106°C
Expansion/ Contraction Rate	5.0mm/m
Fire Rating	Group 4
Cleaning	PSP Cleaner or warm soapy water & soft cloth.

NOTE: Uncontrolled in printed format.