



AlucoSign White ACM



AlucoSign White is a fabrication grade composite panel with a polyethylene core situated between two thin layers of aluminium, which are coated with a polyester paint finish for an outstanding exterior performance.

The result is a lightweight sheet, with excellent flatness, durability & flexural stiffness with a ten year exterior warranty.

Features

- Weather resistant
- Won't warp
- Gloss finish
- Lightweight
- Can be fabricated
- Polyester paint finish
- 10 year exterior warranty

Applications

- Signage
- Corporate signage
- Retail fit out
- Fascias
- Industrial applications

COLOUR RANGE (May not represent the physical product)



PRODUCT RANGE/DIMENSIONS		
Type	Thickness	Length & Width
Gloss White/Service Coat	4.0mm 0.3mm/0.3mm	2440mm x 1220mm
		3050mm x 1500mm
		3650mm x 1500mm
		4050mm x 1500mm
4050mm x 2000mm		
Gloss White/Gloss White	6.0mm 0.3mm/0.3mm	2440mm x 1220mm

PANEL PHYSICAL PROPERTIES	
Type	Result
Weight (4.0mm)	5.7kg/m ² (4.0mm)
Service Temperature	-50°C - 80°C
Expansion/Contraction Rate	2.4.0mm/m
Rigidity	1620kNcm ² /m
Sound Transmission Loss	25dB
Fire Rating	Group 4
Warranty	10 Year Warranty

NOTE: Uncontrolled in printed format.

Version 1.0 - October 2024