

ClearVue

ROOFING SYSTEM



ClearVue in colour
Blue Breeze

DESIGN & INSTALLATION GUIDE

VERSION 1.5 | SEPTEMBER 2026

WWW.PSP.CO.NZ | 0800 786 883

CLEARVUE ROOFING SYSTEM TO BE INSTALLED AND FIXED TO SUITABLE STRUCTURAL SUPPORT, COMPLYING WITH RELEVANT CLAUSES OF THE NZBC AND THE NEW ZEALAND BUILDING ACT.

NOTE: RECOMMENDED ROOF PITCH 5°. MINIMUM ROOF PITCH OF 3°, CONSULT YOUR PSP AGENT FOR SUITABLE APPLICATIONS.

NOTE: As a supplier of building products, PSP provides technical information and product details that a suitably qualified person may rely on when certifying the portion of their design that relates to PSP products and installation requirements. However, PSP does not undertake building design work . As a result, PSP is unable to provide a PS1.


SHEET NUMBER	SHEET TITLE
FIBRE CEMENT	
CAVITY & DIRECT FIXED	
PCV-FC-01	APRON DETAIL
PCV-FC-02	APRON DETAIL - SADDLE BRACKET
PCV-FC-03	APRON DETAIL - STEEL PLATE
PCV-FC-04	BARGE DETAIL
PCV-FC-05	BARGE DETAIL - ALUMINIUM RAFTER

FLASHING WIDTH TABLE - "X"mm
(BASED ON TABLE 7, E2/AS1, 24 DECEMBER 2011)


SITUATION 1:	LOW, MEDIUM OR HIGH WIND ZONES, WHERE ROOF PITCH IS GREATER THAN OR EQUAL TO 5°.		
SITUATION 2:	ALL ROOF PITCHES IN VERY HIGH WIND ZONES. VERY HIGH WIND ZONE WHERE ROOF PITCH IS LESSER THAN OR EQUAL TO 5°.		
SITUATION 3:	ALL ROOF PITCHES IN EXTRA HIGH WIND ZONES.		
	SITUATION 1 (MINIMUM)	SITUATION 2 (MINIMUM)	SITUATION 3 (MINIMUM)
TRANSVERSE FLASHING	130	200	200

PSP - ALUMINIUM & TIMBER RAFTER SPACING TABLE

SHEET THICKNESS	6mm SHEET	8mm SHEET
ALUMINIUM RAFTER SPACING	600 CRS	750 CRS



DIRECT FIX DETAIL



NOTE: Recommended roof pitch 5°. Minimum roof pitch of 3°, consult your PSP agent for suitable applications.


NOTE: All dimensions are in millimeters (mm)

FLASHING WIDTH TABLE - "X"mm
(BASED ON TABLE 7, E2/AS1, 24 DECEMBER 2011)


SITUATION 1:	LOW, MEDIUM OR HIGH WIND ZONES, WHERE ROOF PITCH IS GREATER THAN OR EQUAL TO 5°.		
SITUATION 2:	ALL ROOF PITCHES IN VERY HIGH WIND ZONES. VERY HIGH WIND ZONE WHERE ROOF PITCH IS LESSER THAN OR EQUAL TO 5°.		
SITUATION 3:	ALL ROOF PITCHES IN EXTRA HIGH WIND ZONES.		
	SITUATION 1 (MINIMUM)	SITUATION 2 (MINIMUM)	SITUATION 3 (MINIMUM)
TRANSVERSE FLASHING	130	200	200

PSP - ALUMINIUM & TIMBER RAFTER SPACING TABLE

SHEET THICKNESS	6mm SHEET	8mm SHEET
ALUMINIUM RAFTER SPACING	600 cns	750 cns



DIRECT FIX DETAIL



NOTE: Recommended roof pitch 5°. Minimum roof pitch of 3°, consult your PSP agent for suitable applications.

NOTE: All dimensions are in millimeters (mm)



FLASHING WIDTH TABLE - "X"mm
(BASED ON TABLE 7, E2/AS1, 24 DECEMBER 2011)

SITUATION 1:	LOW, MEDIUM OR HIGH WIND ZONES, WHERE ROOF PITCH IS GREATER THAN OR EQUAL TO 5°.
SITUATION 2:	ALL ROOF PITCHES IN VERY HIGH WIND ZONES. VERY HIGH WIND ZONE WHERE ROOF PITCH IS LESSER THAN OR EQUAL TO 5°.
SITUATION 3:	ALL ROOF PITCHES IN EXTRA HIGH WIND ZONES.

PSP - ALUMINIUM & TIMBER RAFTER SPACING TABLE

SHEET THICKNESS	6mm SHEET	8mm SHEET
ALUMINIUM RAFTER SPACING	600 CRS	750 CRS

	SITUATION 1 (MINIMUM)	SITUATION 2 (MINIMUM)	SITUATION 3 (MINIMUM)
TRANSVERSE FLASHING	130	200	200



NOTE: Recommended roof pitch 5°. Minimum roof pitch of 3°, consult your PSP agent for suitable applications.


NOTE: All dimensions are in millimeters (mm)

FLASHING WIDTH TABLE - "X"mm
(BASED ON TABLE 7, E2/AS1, 24 DECEMBER 2011)


SITUATION 1:	LOW, MEDIUM OR HIGH WIND ZONES, WHERE ROOF PITCH IS GREATER THAN OR EQUAL TO 5°.		
SITUATION 2:	ALL ROOF PITCHES IN VERY HIGH WIND ZONES. VERY HIGH WIND ZONE WHERE ROOF PITCH IS LESSER THAN OR EQUAL TO 5°.		
SITUATION 3:	ALL ROOF PITCHES IN EXTRA HIGH WIND ZONES.		
	SITUATION 1 (MINIMUM)	SITUATION 2 (MINIMUM)	SITUATION 3 (MINIMUM)
TRANSVERSE FLASHING	130	200	200

PSP - ALUMINIUM & TIMBER RAFTER SPACING TABLE

SHEET THICKNESS	6mm SHEET	8mm SHEET
ALUMINIUM RAFTER SPACING	600 crs	750 crs



DIRECT FIX DETAIL



NOTE: Recommended roof pitch 5°. Minimum roof pitch of 3°, consult your PSP agent for suitable applications.


NOTE: All dimensions are in millimeters (mm)

FLASHING WIDTH TABLE - "X"mm
(BASED ON TABLE 7, E2/AS1, 24 DECEMBER 2011)


SITUATION 1:	LOW, MEDIUM OR HIGH WIND ZONES, WHERE ROOF PITCH IS GREATER THAN OR EQUAL TO 5°.		
SITUATION 2:	ALL ROOF PITCHES IN VERY HIGH WIND ZONES. VERY HIGH WIND ZONE WHERE ROOF PITCH IS LESSER THAN OR EQUAL TO 5°.		
SITUATION 3:	ALL ROOF PITCHES IN EXTRA HIGH WIND ZONES.		
	SITUATION 1 (MINIMUM)	SITUATION 2 (MINIMUM)	SITUATION 3 (MINIMUM)
TRANSVERSE FLASHING	130	200	200

PSP - ALUMINIUM & TIMBER RAFTER SPACING TABLE

SHEET THICKNESS	6mm SHEET	8mm SHEET
ALUMINIUM RAFTER SPACING	600 CRS	750 CRS



DIRECT FIX DETAIL



NOTE: Recommended roof pitch 5°. Minimum roof pitch of 3°, consult your PSP agent for suitable applications.

NOTE: All dimensions are in millimeters (mm)